



Item # \_\_\_\_\_

Job \_\_\_\_\_

## SUPER ERECTA SHELF® STEM CASTER CARTS – WIRE SHELVES

- **Stem Caster Carts** combine Super Erecta Shelf® wire shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Variety of Casters Available** : Select the caster that allows the right combination of rollability and maneuverability to suit your requirements. Casters are available in swivel, rigid or brake types. All Metro casters are non-marking and come complete with a 3½" (89mm) donut bumper. Refer to sheet #11.20 for additional caster information.
- **Unique Design** : Open wire surfaces minimize dust accumulation and allow a free circulation of air and greater visibility.
- **Fast, Secure Assembly** : Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of any special tools.
- **Unique Post Design** : New SiteSelect post design provides a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. An easy-to-identify triple groove, every 8 inches, offers a quick way to align all shelves. Bolt leveler on post bottom compensates for uneven surfaces.
- **Adjustability**: Shelves can be adjusted at 1" (25mm) intervals along the entire height of the post.
- **Versatile Construction**: Super Erecta Shelf® wire shelving can change as quickly as your needs change. By using various accessories, hundreds of shelving combinations become possible.



**InterMetro Industries Corporation**  
North Washington Street  
Wilkes-Barre, PA 18705  
www.metro.com

Copyright © 2000 InterMetro Industries Corp.



SUPER ERECTA SHELF®  
**Wire Shelf Carts** (Stem Caster Style)

**11.01**

Job \_\_\_\_\_



SUPER ERECTA SHELF®  
STEM CASTER CARTS – WIRE SHELVES

**STANDARD UNITS**

Consist of four shelves, posts, plastic split sleeves\*, donut bumpers and designated casters.\*\*

Shelf Width (in.)	(mm)	Shelf Length (in.)	(mm)	Catalog Number with Casters			
				Four Swivel Resilient Rubber Casters	Two Swivel Two Brake Resilient Rubber Casters	Four Swivel Polyurethane Casters	Two Swivel Two Brake Polyurethane Casters
<b>With Super Erecta Brite™ Shelves &amp; Plated Posts</b>							
63" (1600mm) Posts – Overall Height 69" (1753mm)							
18	455	36	910	N336ABR	N336BBR	N336DBR	N336EBR
18	455	48	1220	N356ABR	N356BBR	N356DBR	N356EBR
18	455	60	1520	N366ABR	N366BBR	N366DBR	N366EBR
21	530	36	910	N436ABR	N436BBR	N436DBR	N436EBR
21	530	48	1220	N456ABR	N456BBR	N456DBR	N456EBR
21	530	60	1520	N466ABR	N466BBR	N466DBR	N466EBR
24	610	36	910	N536ABR	N536BBR	N536DBR	N536EBR
24	610	48	1220	N556ABR	N556BBR	N556DBR	N556EBR
24	610	60	1520	N566ABR	N566BBR	N566DBR	N566EBR

**With Chrome Shelves & Plated Posts**

63" (1600mm) Posts – Overall Height 69" (1753mm)

18	455	36	910	N336AC	N336BC	N336DC	N336EC
18	455	48	1220	N356AC	N356BC	N356DC	N356EC
18	455	60	1520	N366AC	N366BC	N366DC	N366EC
21	530	36	910	N436AC	N436BC	N436DC	N436EC
21	530	48	1220	N456AC	N456BC	N456DC	N456EC
21	530	60	1520	N466AC	N466BC	N466DC	N466EC
24	610	36	910	N536AC	N536BC	N536DC	N536EC
24	610	48	1220	N556AC	N556BC	N556DC	N556EC
24	610	60	1520	N566AC	N566BC	N566DC	N566EC

**TO ORDER BY COMPONENTS**

- Order shelves from sheet 10.01 or price list. (Will be packed with plastic split sleeves\*.)
- Order stem casters from sheet 11.20 or price list. Donut bumper comes with caster.

\* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see sheet #11.06 or price list.

\*\* Carts with polyurethane casters are designed to hold up to 900 lbs. (408 kg).  
Carts with rubber casters can hold up to 600 lbs. (272 kg).

**Important:** When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

Manufactured by:



**InterMetro Industries Corporation**

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232

Visit Our Web Site: [www.metro.com](http://www.metro.com)

L02-035  
Rev. 9/00  
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

