



Model: _____ Item #: _____ Date: _____
 Project: _____ Qty: _____ Approved By: _____

Royal Series Ice Bins

Royal Series Underbar



KR19-24-10
 Available in 19" or 24" Deep

STANDARD FEATURES

Interior	20 gauge stainless steel. 12" or 15" deep liner
Front Apron	20 gauge stainless steel clad over 20 gauge galvanized steel
Backsplash	20 gauge stainless steel
Back & Bottom	20 gauge galvanized steel
Legs	1-5/8" tubular 16 gauge stainless steel w/ grey plastic bullet foot
Insulation	Foamed-in-place polyurethane
Plumbing	1" IPS drain connection

Ice Bin with Cold Plate

Cold Plate	High performance built-in 10 circuit post mix cold plate. Plate is sealed into bottom. Each circuit is 5/16" OD stainless steel tubing. Two full with remainder to be half circuits. Bump and swedge fittings on ends.
Tubing Access (Cold Plate)	3/4" x 3-1/2" cutout in left side of backsplash
Plumbing	1/2" IPS drain connection. 4" PVC tailpiece provided. PVC tailpiece required to avoid condensation through metal to metal contact.

Cold Plate units supplied with 1/2" x 4" PVC tailpiece.
 1/2" - 20 male threaded



OPTIONAL ACCESSORIES

KR-101	Condiment Tray
KR-103	12" Deep Stainless Steel Divider
KR-113	15" Deep Stainless Steel Divider
KR-108	Perforated Bottom (Ice Bins without Cold Plates)
KR-310	Right End Splash
KR-311	Left End Splash
SC"XX"H	Partial Sliding Cover for 19" Deep Ice Bin (when using bottle wells) ("XX" denotes size of Ice Bin.) Example: 36" Ice Bin would need an SC36H
SC"XX"F	Full Sliding Cover for 19" Deep Ice Bin ("XX" denotes size of Ice Bin.) Example: 36" Ice Bin would need an SC36F
SCD"XX"H	Partial Sliding Cover for 24" Deep Ice Bin (when using bottle wells) ("XX" denotes size of Ice Bin.) Example: KR24-30 would need a SCD30H
SCD"XX"F	Full Sliding Cover for 24" Deep Ice Bin ("XX" denotes size of Ice Bin.) Example: KR24-30 would need a SCD30F
KR-401	Cap Catcher and Opener
KR-406	Faucet installed over Ice Bin for meltdown
KR-501	Towel Ring
Built-In Cold Plate	(See features to the left)
KR-519	18" Garnish Station w/ Sliding Cover
KR-520	24" Garnish Station w/ Sliding Cover
KR-521	30" Garnish Station w/ Sliding Cover
RS-"XX"	Single Speed Rail ("XX denotes size of ice bin.)
RD-"XX"	Double Speed Rail ("XX denotes size of ice bin.)
30-550	3 Compartment bottle well for ice bin (Fits KR19 Ice Bins)
30-502	3 Compartment bottle well for ice bin (2 pack) (Fits KR19 Ice Bins)



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Royal Series Ice Bins

Royal Series Underbar

Model Numbers	Overall Length (A)	Left Side to Drain (B)	Interior Dimensions (C)	Inside Depth (D)	Outside Depth (E)	Ice Capacity (lbs.)	Cold Plate Circuits	Weight (lbs.)
*KR19-6	6"	3"	15" x 4"	10"	11 1/2"	20	N/A	20
*KR19-8	8"	4"	15" x 6"	10"	11 1/2"	22	N/A	25
KR19-12	12"	9"	15" x 10"	10"	11 1/2"	25	N/A	35
KR19-18	18"	9"	15" x 16"	12"	13 1/2"	50	N/A	55
KR19-24	24"	12"	15" x 22"	12"	13 1/2"	80	N/A	60
KR19-30	30"	15"	15" x 28"	12"	13 1/2"	97	N/A	80
KR19-36	36"	18"	15" x 34"	12"	13 1/2"	115	N/A	95
KR19-42	42"	21"	15" x 40"	12"	13 1/2"	135	N/A	115
KR19-48	48"	24"	15" x 46"	12"	13 1/2"	160	N/A	130
<hr/>								
KR19-18-7	18"	9"	15" x 16"	12"	13 1/2"	50	7	75
KR19-24-10	24"	12"	15" x 22"	12"	16 1/2"	80	10	166
KR19-30-10	30"	15"	15" x 28"	12"	16 1/2"	97	10	185
KR19-36-10	36"	18"	15" x 34"	12"	16 1/2"	115	10	199
KR19-42-10	42"	21"	15" x 40"	12"	16 1/2"	135	10	235
KR19-48-10	48"	24"	15" x 46"	12"	16 1/2"	160	10	249
<hr/>								
KR19-24DP	24"	12"	15" x 22"	15"	16 1/2"	100	N/A	75
KR19-30DP	30"	15"	15" x 28"	15"	16 1/2"	120	N/A	100
KR19-36DP	36"	18"	15" x 34"	15"	16 1/2"	138	N/A	125
KR19-48DP	48"	24"	15" x 46"	15"	16 1/2"	178	N/A	216
<hr/>								
KR19-24DP-10	24"	12"	15" x 22"	15"	19 1/2"	100	10	188
KR19-30DP-10	30"	15"	15" x 28"	15"	19 1/2"	120	10	225
KR19-36DP-10	36"	18"	15" x 34"	15"	19 1/2"	138	10	270
KR19-48DP-10	48"	24"	15" x 46"	15"	19 1/2"	178	10	296

19" Deep

*KR19-6 must ship attached at factory. Cannot ship loose. Free standing unit not available.
 *KR19-8 must ship attached at factory. Cannot ship loose. Free standing unit not available.

Model Numbers	Overall Length (A)	Left Side to Drain (B)	Interior Dimensions (C)	Inside Depth (D)	Outside Depth (E)	Ice Capacity (lbs.)	Cold Plate Circuits	Weight (lbs.)
*KR24-6	6"	3"	15" x 4"	10"	11 1/2"	20	N/A	20
KR24-12	12"	6"	20" x 10"	10"	11 1/2"	42	N/A	55
KR24-18	18"	9"	20" x 16"	12"	13 1/2"	64	N/A	70
KR24-24	24"	12"	20" x 22"	12"	13 1/2"	85	N/A	80
KR24-30	30"	15"	20" x 28"	12"	13 1/2"	106	N/A	95
<hr/>								
KR24-18-7	18"	9"	20" x 16"	12"	16 1/2"	64	7	90
KR24-24-10	24"	12"	20" x 22"	12"	16 1/2"	85	10	145
KR24-30-10	30"	15"	20" x 28"	12"	16 1/2"	106	10	160
<hr/>								
KR24-18DP	18"	9"	20" x 16"	15"	16 1/2"	91	N/A	76
KR24-24DP	24"	12"	20" x 22"	15"	16 1/2"	117	N/A	80
KR24-30DP	30"	15"	20" x 28"	15"	16 1/2"	147	N/A	95
KR24-36DP	36"	18"	20" x 34"	15"	16 1/2"	183	N/A	114
<hr/>								
KR24-18DP-7	18"	9"	20" x 16"	15"	19 1/2"	91	7	133
KR24-24DP-10	24"	12"	20" x 22"	15"	19 1/2"	121	10	148
KR24-30DP-10	30"	15"	20" x 28"	15"	19 1/2"	153	10	162
KR24-36DP-10	36"	18"	20" x 34"	15"	19 1/2"	183	10	171

24" Deep

*KR24-6 must ship attached at factory. Cannot ship loose. Free standing unit not available.
 *Other size length available upon request.

Mechanical Requirements:

1" IPS drain connection without Cold Plate. 1/2" IPS drain connection with Cold Plate



Conforms to NSF Std. 2